

## **TERMS AND CONDITIONS**

### **CAUTION**

Direct contact between pressure treated lumber and metal roofing must be avoided in order to prevent potential corrosion.

### **CRITICAL APPEARANCE APPLICATIONS**

The reverse roll coater provides precise application of the acrylic film, assuring uniform film thickness. However, uniform visual appearance of unpainted Galvalume sheet cannot be guaranteed. The normally occurring variations in surface appearance typical of all hot-dip Galvalume will still be present and will not be masked by the thin, clear acrylic film. If Galvalume visual appearance is critical, then pre-painted Galvalume sheet should be ordered.

### **WOOD DECK**

Must be minimum of ½" structural plywood or OSB

### **JOB SITE DELIVERY AVAILABLE**

Customer must have fork lift availability.

### **OIL CANNING**

A certain amount of waviness, called oil canning, is inherent in products made from coiled metal. Job site conditions such as temperature variations, misaligned substrates and improper installation may aggravate the condition. Oil canning does not affect the structural integrity, or finish of the material and is not a cause of rejection.

### **CANCELLATIONS**

Marlyn will honor cancellations prior to manufacturing. Any order which has already been manufactured is the property of the purchaser.

### **CLAIMS**

All claims of shortage, damage, etc. must be made within 48 hours of the date of receipt. Claims must be accompanied by a copy of the bill of lading verified by the shipper which must indicate shortages of damages as received. Marlyn cannot honor shortage or damage claims on freight carriers unless the carrier's paperwork is duly noted.

### **RETURN POLICY**

All Marlyn panel orders are considered "special order products." Special order products cannot be returned.

### **WARRANTED PRODUCTS**

Marlyn will be happy to provide you with a draft copy of our warranty for Acrylic Coated Galvalume or painted products. Failure to request this draft will indicate your acceptance of the contents therein.

### **INDEMNITY**

All prices and/or designs are subject to change without notice.

### **SAFETY**

Marlyn recommends the compliance with the Florida Fall Protection Act.

### **CLEANING PAINTED SURFACES**

Marlyn recommends that there be a systematic fresh water rinse maintenance program in effect in the areas of high salt concentration (such as adjacent to the seasonal and/or industrial atmospheres) so as to prevent the accumulation of concentrated mineral deposit. Cleaning will generally restore the appearance of the buildings and render repainting unnecessary. An occasional light cleaning will also help maintain an aesthetically pleasing appearance.

### **DISCLAIMER**

While we make every attempt to accuracy, we are not responsible for typographical or printing errors.

### **BLEEDING**

Filings from screw installations and cutting fragments of the panels must be cleared off the panels to avoid rust marks or "bleeding" on the panels. Failure to comply with the above procedures relieves Marlyn of responsibility for any resulting damaged to or deterioration of the finish. These void out any paint or finish warranty.